



MPA / T (CBB20/19) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■結構圖 Construction



■尺寸代碼 Dimensions Code



■特性 | Feature

金屬化聚丙烯膜, 無感捲繞結構, 軸向
較低損耗值、低 ESR、高 IR
卓越的高頻性能
優良的溫度特性
自愈性特質, 可靠性高

Metalized polypropylene film, non-inductive type, axial
Self-healing property, Low DF, low ESR、High IR
Excellent frequency characteristics
Excellent temperature characteristics
High reliable because of its excellent Self-Healing performance

■推薦應用領域 | Typical Application

應用於音訊分頻電路
應用於高頻和大電流的電子電路
廣泛應用於一般電子電路中

Audio-circuit
High frequency and high current circuits
General purpose circuits

技術要求參照標準 Specification Reference Standard	GB/T 10190 (IEC 60384-16)
氣候類別 Climatic Category	55/100/21
工作溫度範圍 Operation Temperature Range	-55°C~100°C (+85°C~+100°C : decreasing factor1.25% per°C for U _R)
額定電壓 Rated Voltage	250 / 400 / 630 / 1000 / 1250 VDC
電容量範圍 Capacitance Range	0.001μF~15μF
電容量偏差 Capacitance Tolerance	±5%(J) 、 ±10%(K)
耐電壓 Voltage Proof	1.5U _R , 5sec
絕緣電阻 Insulation Resistance	CR≤0.33μF,IR≥15000MΩ ;CR>0.33μF,IR≥5000 MΩ/CAP(μF)
損耗角正切 Dissipation Factor	0.1% Max, at 1KHz and 20°C

MPA (CBB20) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

250VDC

容量μF	W	T	H	d	產品代碼 Part No.
0.033	13	3.3	6.1	0.6	MPA333#2E-13***++
0.047	13	4	6.8	0.6	MPA473#2E-13***++
0.047	15	3.4	7	0.6	MPA473#2E-15***++
0.068	15	3.9	8.3	0.6	MPA683#2E-15***++
0.1	15	4.8	9.3	0.6	MPA104#2E-15***++
0.15	20	4.1	8.5	0.8	MPA154#2E-20***++
0.22	20	5.1	9.5	0.8	MPA224#2E-20***++
0.22	25	4.1	4.5	0.8	MPA224#2E-25***++
0.33	20	5.9	11.9	0.8	MPA334#2E-20***++
0.33	25	4.6	10.6	0.8	MPA334#2E-25***++
0.47	20	7.3	13.3	0.8	MPA474#2E-20***++
0.47	25	5.7	11.7	0.8	MPA474#2E-25***++
0.68	25	7.1	13.1	0.8	MPA684#2E-25***++
0.68	28	6.1	12.1	0.8	MPA684#2E-28***++
1	25	8.4	15.9	0.8	MPA105#2E-25***++
1	28	7.4	15	0.8	MPA105#2E-28***++
1	32	6.6	14.1	0.8	MPA105#2E-32***++
1.5	28	9.6	17.2	0.8	MPA155#2E-28***++
1.5	32	8.5	16	0.8	MPA155#2E-32***++
2.2	32	10.1	19.2	0.8	MPA225#2E-32***++
2.2	36	9.1	18.2	0.8	MPA225#2E-36***++
3.3	32	13	22.2	0.8	MPA335#2E-32***++
3.3	36	11.7	20.9	0.8	MPA335#2E-36***++
3.3	46	9.6	18.7	0.8	MPA335#2E-46***++
4.7	36	14.6	23.8	0.8	MPA475#2E-36***++
4.7	46	11.9	21	0.8	MPA475#2E-46***++
4.7	56	10.3	19.4	0.8	MPA475#2E-56***++
6.8	46	14.3	22.2	0.8	MPA685#2E-46***++
6.8	56	12.4	21.5	0.8	MPA685#2E-56***++
10	56	20.7	29	0.8	MPA106#2E-56***++

400VDC

容量μF	W	T	H	d	產品代碼 Part No.
0.022	13	3.2	6	0.6	MPA223#2G-13***++
0.033	13	4	6.8	0.6	MPA333#2G-13***++
0.033	15	3.4	6.2	0.6	MPA333#2G-15***++
0.047	13	4.8	7.6	0.6	MPA473#2G-13***++
0.047	15	4.2	7.7	0.6	MPA473#2G-15***++
0.068	15	5.1	8.7	0.6	MPA683#2G-15***++
0.068	20	3.3	7.6	0.8	MPA683#2G-20***++
0.1	15	6.4	9.9	0.6	MPA104#2G-15***++
0.1	20	4	8.4	0.8	MPA104#2G-20***++
0.15	20	5.1	9.5	0.8	MPA154#2G-20***++
0.15	25	4	8.4	0.8	MPA154#2G-25***++
0.22	20	6.4	10.7	0.8	MPA224#2G-20***++
0.22	25	4.9	9.3	0.8	MPA224#2G-25***++
0.22	28	4.4	8.9	0.8	MPA224#2G-28***++
0.33	20	7.4	13.3	0.8	MPA334#2G-20***++
0.33	25	5.8	11.7	0.8	MPA334#2G-25***++
0.33	28	5.2	11.1	0.8	MPA334#2G-28***++
0.47	20	9.1	15	0.8	MPA474#2G-20***++
0.47	25	7.1	13.1	0.8	MPA474#2G-25***++
0.47	28	6.4	12.3	0.8	MPA474#2G-28***++
0.68	25	8.2	15.7	0.8	MPA684#2G-25***++
0.68	28	7.4	14.9	0.8	MPA684#2G-28***++
1	25	10.5	18	0.8	MPA105#2G-25***++
1	28	9.4	16.9	0.8	MPA105#2G-28***++
1	32	8.3	15.8	0.8	MPA105#2G-32***++
1.5	28	11.2	20.3	0.8	MPA155#2G-28***++
1.5	32	10	19	0.8	MPA155#2G-32***++
2.2	32	12.7	21.8	0.8	MPA225#2G-32***++
2.2	36	11.4	20.5	0.8	MPA225#2G-36***++
3.3	32	16.3	25.3	0.8	MPA335#2G-32***++
3.3	36	14.7	23.8	0.8	MPA335#2G-36***++
3.3	46	12	21.1	0.8	MPA335#2G-46***++
4.7	46	14.9	24	0.8	MPA475#2G-46***++
4.7	56	12.9	21.9	0.8	MPA475#2G-56***++
6.8	46	18.7	27.8	0.8	MPA685#2G-46***++
6.8	56	16.1	25.2	0.8	MPA685#2G-56***++
10	56	20.3	29.4	0.8	MPA106#2G-56***++

MPA (CBB20) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

630VDC

容量μF	W	T	H	d	產品代碼 Part No.
0.01	13	3.6	6.9	0.6	MPA103#2J-13***++
0.01	15	3.2	7.5	0.6	MPA103#2J-15***++
0.015	13	3.6	7.1	0.6	MPA153#2J-13***++
0.015	15	3.3	7.6	0.6	MPA153#2J-15***++
0.022	13	4.5	7.1	0.6	MPA223#2J-13***++
0.022	15	3.6	7.9	0.6	MPA223#2J-15***++
0.033	15	4.5	8.7	0.6	MPA333#2J-15***++
0.047	15	5.8	9.3	0.6	MPA473#2J-15***++
0.047	20	3.6	8	0.8	MPA473#2J-20***++
0.068	20	4.6	8.8	0.8	MPA683#2J-20***++
0.068	25	3.6	9.5	0.8	MPA683#2J-25***++
0.1	20	5	10.9	0.8	MPA104#2J-20***++
0.1	25	3.9	9.9	0.8	MPA104#2J-25***++
0.15	20	5.9	13.4	0.8	MPA154#2J-20***++
0.15	25	5	10.9	0.8	MPA154#2J-25***++
0.22	25	5.8	13.3	0.8	MPA224#2J-25***++
0.22	28	5.2	12.7	0.8	MPA224#2J-28***++
0.33	25	7.4	15	0.8	MPA334#2J-25***++
0.33	28	6.7	14.2	0.8	MPA334#2J-28***++
0.47	25	8.7	17.8	0.8	MPA474#2J-25***++
0.47	28	7.7	16.8	0.8	MPA474#2J-28***++
0.47	32	6.8	15.9	0.8	MPA474#2J-32***++
0.68	28	9.8	18.9	0.8	MPA684#2J-28***++
0.68	32	8.7	17.8	0.8	MPA684#2J-32***++
1	32	11	20.1	0.8	MPA105#2J-32***++
1	36	10	19	0.8	MPA105#2J-36***++
1.5	32	14.3	23.2	0.8	MPA155#2J-32***++
1.5	36	12.9	21.8	0.8	MPA155#2J-36***++
2.2	36	16.3	25.2	0.8	MPA225#2J-36***++
2.2	46	13.4	22.3	0.8	MPA225#2J-46***++
2.2	56	11.5	20.4	0.8	MPA225#2J-56***++
3.3	46	17.1	26	0.8	MPA335#2J-46***++
3.3	56	14.7	23.7	0.8	MPA335#2J-56***++
4.7	46	21	30	0.8	MPA475#2J-46***++
4.7	56	18.2	27.2	0.8	MPA475#2J-56***++

1000VDC

容量μF	W	T	H	d	產品代碼 Part No.
0.0033	13	3.1	5.9	0.6	MPA332#3A-13***++
0.0047	13	4	7	0.6	MPA472#3A-13***++
0.0047	15	2.9	7.3	0.6	MPA472#3A-15***++
0.0068	15	3.6	8	0.6	MPA682#3A-15***++
0.01	15	5	8.9	0.6	MPA103#3A-15***++
0.01	20	3	7.4	0.8	MPA103#3A-20***++
0.015	20	3.4	9.3	0.8	MPA153#3A-20***++
0.022	20	4.2	14.4	0.8	MPA223#3A-20***++
0.033	20	6.6	11.4	0.8	MPA333#3A-20***++
0.033	25	4.8	10.2	0.8	MPA333#3A-25***++
0.047	20	6.1	13.7	0.8	MPA473#3A-20***++
0.047	25	4.7	12.3	0.8	MPA473#3A-25***++
0.068	25	4.7	13.5	0.8	MPA683#3A-25***++
0.1	25	8.1	15.1	0.8	MPA104#3A-25***++
0.1	28	7.4	14.3	0.8	MPA104#3A-28***++
0.15	28	8.8	17.4	0.8	MPA154#3A-28***++
0.15	32	7.8	16.3	0.8	MPA154#3A-32***++
0.22	32	9.8	18.3	0.8	MPA224#3A-32***++
0.22	36	8.8	17.4	0.8	MPA224#3A-36***++
0.33	32	12.5	21	0.8	MPA334#3A-32***++
0.33	36	11.2	19.7	0.8	MPA334#3A-36***++
0.33	46	9.3	17.8	0.8	MPA334#3A-46***++
0.47	36	13.9	22.5	0.8	MPA474#3A-36***++
0.47	46	11.5	20	0.8	MPA474#3A-46***++
0.47	56	9.9	18.4	0.8	MPA474#3A-56***++
0.68	36	17.3	25.8	0.8	MPA684#3A-36***++
0.68	46	14.3	22.8	0.8	MPA684#3A-46***++
0.68	56	12.3	20.9	0.8	MPA684#3A-56***++
1	46	17.9	26.4	0.8	MPA105#3A-46***++
1	56	15.5	24.1	0.8	MPA105#3A-56***++
1.5	56	19.6	28.2	0.8	MPA155#3A-56***++

MPA (CBB20) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

1250VDC

容量 μ F	W	T	H	d	產品代碼 Part No.
0.001	13	3	5.6	0.6	MPA102#3B-13***+++
0.0015	13	3.2	5.8	0.6	MPA152#3B-13***+++
0.0022	13	3.5	6.3	0.6	MPA222#3B-13***+++
0.0022	15	3.3	6.1	0.6	MPA222#3B-15***+++
0.0033	13	4.2	7	0.6	MPA332#3B-13***+++
0.0033	15	3.7	7.3	0.6	MPA332#3B-15***+++
0.0047	15	3.2	9.1	0.6	MPA472#3B-15***+++
0.0068	15	4	9.9	0.6	MPA682#3B-15***+++
0.0068	20	3	7.4	0.8	MPA682#3B-20***+++
0.01	20	3.3	9.2	0.8	MPA103#3B-20***+++
0.015	20	4.3	10.1	0.8	MPA153#3B-20***+++
0.022	20	6	11.2	0.8	MPA223#3B-20***+++
0.022	25	3.8	11.2	0.8	MPA223#3B-25***+++
0.033	20	6.9	13.7	0.8	MPA333#3B-20***+++
0.033	25	4.7	12.3	0.8	MPA333#3B-25***+++
0.047	25	6	13.5	0.8	MPA473#3B-25***+++
0.047	28	5.3	12.8	0.8	MPA473#3B-28***+++
0.068	25	8.3	15.1	0.8	MPA683#3B-25***+++

1250VDC

容量 μ F	W	T	H	d	產品代碼 Part No.
0.068	28	6.7	14.2	0.8	MPA683#3B-28***+++
0.1	28	7.9	17	0.8	MPA104#3B-28***+++
0.1	32	7.7	16.1	0.8	MPA104#3B-32***+++
0.15	32	9.8	18.2	0.8	MPA154#3B-32***+++
0.15	36	8.9	17.3	0.8	MPA154#3B-36***+++
0.22	32	12.3	20.7	0.8	MPA224#3B-32***+++
0.22	36	11.2	19.5	0.8	MPA224#3B-36***+++
0.33	32	15.6	24	0.8	MPA334#3B-32***+++
0.33	36	14.2	22.5	0.8	MPA334#3B-36***+++
0.33	46	11	20.1	0.8	MPA334#3B-46***+++
0.47	36	17.4	25.7	0.8	MPA474#3B-36***+++
0.47	46	13.5	22.6	0.8	MPA474#3B-46***+++
0.47	56	11.8	20.8	0.8	MPA474#3B-56***+++
0.68	46	10.8	19.5	0.8	MPA684#3B-46***+++
0.68	56	11.8	20.8	0.8	MPA684#3B-56***+++
1	46	13.6	22.4	0.8	MPA105#3B-46***+++
1	56	11.8	20.5	0.8	MPA105#3B-56***+++
1.5	56	15	23.7	0.8	MPA155#3B-56***+++

注:# 表容量偏差；- 表引線型式；*** 表引線長度及包裝方式；+++表內部管理碼

Note: # Capacitance tolerance code ; - Forming lead shapes ; *** Lead length and packaging ; +++ Internal use

注:本公司更改設計規格不予事先通知, 以上數據僅作選型參考, 以實際規格書為準

Note: Design, specifications are subject to change without notice, the above parameters for reference only, see the approval sheet for details.

注:可依需求製作特殊規格

Note: Special size or items on request.

MPT (CBB19) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

250VDC

容量μF	W	D	d	產品代碼 Part No.
0.033	13	5.6	0.6	MPT333#2E-13***++
0.047	13	5.8	0.6	MPT473#2E-13***++
0.068	13	6.6	0.6	MPT683#2E-13***++
0.068	15	6.3	0.6	MPT683#2E-15***++
0.1	15	7.3	0.6	MPT104#2E-15***++
0.1	20	5.9	0.8	MPT104#2E-20***++
0.15	15	8.5	0.6	MPT154#2E-15***++
0.15	20	6.7	0.8	MPT154#2E-20***++
0.22	20	7.7	0.8	MPT224#2E-20***++
0.22	25	6.6	0.8	MPT224#2E-25***++
0.33	20	9	0.8	MPT334#2E-20***++
0.33	25	7.7	0.8	MPT334#2E-25***++
0.47	20	10.5	0.8	MPT474#2E-20***++
0.47	25	8.8	0.8	MPT474#2E-25***++
0.47	28	8.2	0.8	MPT474#2E-28***++
0.68	25	10.3	0.8	MPT684#2E-25***++
0.68	28	9.5	0.8	MPT684#2E-28***++
0.68	32	8.8	0.8	MPT684#2E-32***++
1	25	12.2	0.8	MPT105#2E-25***++
1	28	11.2	0.8	MPT105#2E-28***++
1	32	10.3	0.8	MPT105#2E-32***++
1.5	28	13.4	0.8	MPT155#2E-28***++
1.5	32	12.3	0.8	MPT155#2E-32***++
1.5	36	11.5	0.8	MPT155#2E-36***++
2.2	32	14.6	0.8	MPT225#2E-32***++
2.2	36	13.6	0.8	MPT225#2E-36***++
2.2	46	11.8	0.8	MPT225#2E-46***++
3.3	36	16.3	0.8	MPT335#2E-36***++
3.3	46	14.1	0.8	MPT335#2E-46***++
3.3	56	12.7	0.8	MPT335#2E-56***++
4.7	46	16.5	0.8	MPT475#2E-46***++
4.7	56	14.8	0.8	MPT475#2E-56***++
6.8	46	19.6	0.8	MPT685#2E-46***++
6.8	56	17.5	0.8	MPT685#2E-56***++
10	46	23.5	0.8	MPT106#2E-46***++
10	56	21	0.8	MPT106#2E-56***++
15	56	25.4	0.8	MPT156#2E-56***++

400VDC

容量μF	W	D	d	產品代碼 Part No.
0.033	13	5.9	0.6	MPT333#2G-13***++
0.033	15	5.6	0.6	MPT333#2G-15***++
0.047	13	6.6	0.6	MPT473#2G-13***++
0.047	15	6.3	0.6	MPT473#2G-15***++
0.068	15	7.3	0.6	MPT683#2G-15***++
0.068	20	5.8	0.8	MPT683#2G-20***++
0.1	20	6.6	0.8	MPT104#2G-20***++
0.1	25	5.8	0.8	MPT104#2G-25***++
0.15	20	7.6	0.8	MPT154#2G-20***++
0.15	25	6.6	0.8	MPT154#2G-25***++
0.22	20	8.9	0.8	MPT224#2G-20***++
0.22	25	7.6	0.8	MPT224#2G-25***++
0.22	28	7.1	0.8	MPT224#2G-28***++
0.33	25	8.9	0.8	MPT334#2G-25***++
0.33	28	8.2	0.8	MPT334#2G-28***++
0.33	32	7.6	0.8	MPT334#2G-32***++
0.47	25	10.2	0.8	MPT474#2G-25***++
0.47	28	9.5	0.8	MPT474#2G-28***++
0.47	32	8.8	0.8	MPT474#2G-32***++
0.68	28	11.2	0.8	MPT684#2G-28***++
0.68	32	10.2	0.8	MPT684#2G-32***++
0.68	36	9.7	0.8	MPT684#2G-36***++
1	32	12	0.8	MPT105#2G-32***++
1	36	11.3	0.8	MPT105#2G-36***++
1	46	9.9	0.8	MPT105#2G-46***++
1.5	32	14.4	0.8	MPT155#2G-32***++
1.5	36	13.4	0.8	MPT155#2G-36***++
1.5	46	11.8	0.8	MPT155#2G-46***++
2.2	36	15.9	0.8	MPT225#2G-36***++
2.2	46	13.8	0.8	MPT225#2G-46***++
2.2	56	12.4	0.8	MPT225#2G-56***++
3.3	46	16.6	0.8	MPT335#2G-46***++
3.3	56	14.9	0.8	MPT335#2G-56***++
4.7	46	19.5	0.8	MPT475#2G-46***++
4.7	56	17.4	0.8	MPT475#2G-56***++
6.8	46	23.1	0.8	MPT685#2G-46***++
6.8	56	20.6	0.8	MPT685#2G-56***++

MPT (CBB19) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

630VDC

容量μF	W	D	d	產品代碼 Part No.
0.015	13	5.6	0.6	MPT153#2J-13***++
0.022	13	6.5	0.6	MPT223#2J-13***++
0.022	15	6	0.6	MPT223#2J-15***++
0.033	15	6.9	0.6	MPT333#2J-15***++
0.033	20	5.7	0.8	MPT333#2J-20***++
0.047	15	7.9	0.6	MPT473#2J-15***++
0.047	20	6.3	0.8	MPT473#2J-20***++
0.068	20	7.2	0.8	MPT683#2J-20***++
0.068	25	6.2	0.8	MPT683#2J-25***++
0.1	20	8.2	0.8	MPT104#2J-20***++
0.1	25	7.1	0.8	MPT104#2J-25***++
0.1	28	6.6	0.8	MPT104#2J-28***++
0.15	20	9.6	0.8	MPT154#2J-20***++
0.15	25	8.2	0.8	MPT154#2J-25***++
0.15	28	7.7	0.8	MPT154#2J-28***++
0.22	25	9.5	0.8	MPT224#2J-25***++
0.22	28	8.9	0.8	MPT224#2J-28***++
0.33	25	11.3	0.8	MPT334#2J-25***++
0.33	28	10.5	0.8	MPT334#2J-28***++
0.33	32	9.6	0.8	MPT334#2J-32***++
0.47	28	12.2	0.8	MPT474#2J-28***++
0.47	32	11.2	0.8	MPT474#2J-32***++
0.47	36	10.5	0.8	MPT474#2J-36***++
0.68	32	13.1	0.8	MPT684#2J-32***++
0.68	36	12.3	0.8	MPT684#2J-36***++
1	32	15.5	0.8	MPT105#2J-32***++
1	36	14.6	0.8	MPT105#2J-36***++
1	46	12.6	0.8	MPT105#2J-46***++
1.5	36	17.5	0.8	MPT155#2J-36***++
1.5	46	15.1	0.8	MPT155#2J-46***++
2.2	46	17.9	0.8	MPT225#2J-46***++
2.2	56	16	0.8	MPT225#2J-56***++
3.3	46	21.6	0.8	MPT335#2J-46***++
3.3	56	19.2	0.8	MPT335#2J-56***++
4.7	56	22.7	0.8	MPT475#2J-56***++
6.8	56	26.9	0.8	MPT685#2J-56***++

1000VDC

容量μF	W	D	d	產品代碼 Part No.
0.0047	13	5.8	0.6	MPT472#3A-13***++
0.0068	13	6.6	0.6	MPT682#3A-13***++
0.0068	15	6.2	0.6	MPT682#3A-15***++
0.01	13	7.6	0.6	MPT103#3A-13***++
0.01	15	7.2	0.6	MPT103#3A-15***++
0.015	15	8.4	0.6	MPT153#3A-15***++
0.015	20	5.9	0.8	MPT153#3A-20***++
0.022	20	7.6	0.8	MPT223#3A-20***++
0.033	20	8.9	0.8	MPT333#3A-20***++
0.033	25	7.6	0.8	MPT333#3A-25***++
0.047	20	10.3	0.8	MPT473#3A-20***++
0.047	25	8.7	0.8	MPT473#3A-25***++
0.068	25	10.2	0.8	MPT683#3A-25***++
0.068	28	9.4	0.8	MPT683#3A-28***++
0.1	28	11.1	0.8	MPT104#3A-28***++
0.1	32	10.3	0.8	MPT104#3A-32***++
0.15	32	12.1	0.8	MPT154#3A-32***++
0.15	36	11.4	0.8	MPT154#3A-36***++
0.22	36	13.3	0.8	MPT224#3A-36***++
0.22	46	11.4	0.8	MPT224#3A-46***++
0.33	36	15.9	0.8	MPT334#3A-36***++
0.33	46	13.8	0.8	MPT334#3A-46***++
0.47	46	16.1	0.8	MPT474#3A-46***++
0.47	56	14.5	0.8	MPT474#3A-56***++
0.68	46	19.1	0.8	MPT684#3A-46***++
0.68	56	17.1	0.8	MPT684#3A-56***++
1	56	20.4	0.8	MPT105#3A-56***++
1.5	56	24.7	0.8	MPT155#3A-56***++

MPT (CBB19) series 軸向金屬化聚丙烯膜電容器 Axial Leaded Metallized Polypropylene Film Capacitor



■外型尺寸 Dimensions (mm)

1250VDC

容量μF	W	D	d	產品代碼 Part No.
0.001	13	5.6	0.6	MPT102#3B-13***+++
0.0015	13	5.6	0.6	MPT152#3B-13***+++
0.0022	13	5.6	0.6	MPT222#3B-13***+++
0.0033	13	5.8	0.6	MPT332#3B-13***+++
0.0047	13	6.6	0.6	MPT472#3B-13***+++
0.0068	15	7.1	0.6	MPT682#3B-15***+++
0.0068	20	5.8	0.8	MPT682#3B-20***+++
0.01	15	8.3	0.6	MPT103#3B-15***+++
0.01	20	6.6	0.8	MPT103#3B-20***+++
0.015	20	7.6	0.8	MPT153#3B-20***+++
0.022	20	8.7	0.8	MPT223#3B-20***+++
0.022	25	7.5	0.8	MPT223#3B-25***+++
0.033	20	10.2	0.8	MPT333#3B-20***+++
0.033	25	8.7	0.8	MPT333#3B-25***+++
0.047	25	10.1	0.8	MPT473#3B-25***+++

1250VDC

容量μF	W	D	d	產品代碼 Part No.
0.047	28	9.3	0.8	MPT473#3B-28***+++
0.068	28	10.9	0.8	MPT683#3B-28***+++
0.068	32	10	0.8	MPT683#3B-32***+++
0.1	28	12.9	0.8	MPT104#3B-28***+++
0.1	32	11.9	0.8	MPT104#3B-32***+++
0.15	32	14.1	0.8	MPT154#3B-32***+++
0.15	36	13.2	0.8	MPT154#3B-36***+++
0.22	36	15.6	0.8	MPT224#3B-36***+++
0.22	46	13.6	0.8	MPT224#3B-46***+++
0.33	46	16.2	0.8	MPT334#3B-46***+++
0.33	56	14.5	0.8	MPT334#3B-56***+++
0.47	46	19	0.8	MPT474#3B-46***+++
0.47	56	17	0.8	MPT474#3B-56***+++
0.68	56	20.2	0.8	MPT684#3B-56***+++
1	56	24.1	0.8	MPT105#3B-56***+++

注:# 表容量偏差 ; - 表引線型式 ; *** 表引線長度及包裝方式 ; +++表內部管理碼

Note: # Capacitance tolerance code ; - Forming lead shapes ; *** Lead length and packaging ; +++ Internal use

注:本公司更改設計規格不予事先通知, 以上數據僅作選型參考, 以實際規格書為準

Note: Design, specifications are subject to change without notice, the above parameters for reference only, see the approval sheet for details.

注:可依需求製作特殊規格

Note: Special size or items on request.