



MEB (CL23B) series 小型化金屬化聚酯膜電容器 Miniaturized Metallized Polyester Film Capacitor



■結構圖 Construction



■尺寸代碼 Dimensions Code



■特性 | Feature

金屬化聚酯膜, 無感捲繞結構
體積小、自愈性好
抗脈衝能力強
高可靠性
塑膠外殼(UL94 V-0), 阻燃環氧填充

Metallized polyester film, non-inductive wound construction
Small size and excellent self-healing property
High dv/dt ability
High reliability
Plastic case (UL94 V-0) , Epoxy resin sealing

■推薦應用領域 | Typical Application

旁路、隔直、耦合、退耦
用於直流或脈動電路中, 特別適用於程式控制交換機
LCD 監視器整流, 汽車直流馬達抑制干擾

By-passing, blocking, coupling, decoupling
For DC or pulse circuit, especially suitable for
program-controlled switches
Invert for LCD monitors, automotive DC motor
suppression

技術要求參照標準 Specification Reference Standard	GB/T 7332 (IEC 60384-2)
氣候類別 Climatic Category	55/105/56
工作溫度範圍 Operation Temperature Range	-55°C~105°C (+85°C~+105°C : decreasing factor 1.25% per°C for U _R)
額定電壓 Rated Voltage	63 / 100 / 250 / 400 VDC
電容量範圍 Capacitance Range	0.001μF~1μF
電容量偏差 Capacitance Tolerance	±5%(J) 、 ±10%(K)
耐電壓 Voltage Proof	1.5U _R , 5sec
絕緣電阻 Insulation Resistance	CR≤0.33μF, IR≥15000MΩ ; CR>0.33μF, IR≥5000 MΩ/CAP(μF)
損耗角正切 Dissipation Factor	1% Max , at 1KHz and 20°C

MEB (CL23B) series 小型化金屬化聚酯膜電容器 Miniaturized Metallized Polyester Film Capacitor



■外型尺寸 Dimensions (mm)

63VDC (40VAC)

容量μF	W	H	T	P	d	產品代碼 Part No.
0.001	7.2	6.5	2.5	5	0.5	MEB102#1J-05***+++
0.0015	7.2	6.5	2.5	5	0.5	MEB152#1J-05***+++
0.0022	7.2	6.5	2.5	5	0.5	MEB222#1J-05***+++
0.0027	7.2	6.5	2.5	5	0.5	MEB272#1J-05***+++
0.0033	7.2	6.5	2.5	5	0.5	MEB332#1J-05***+++
0.0039	7.2	6.5	2.5	5	0.5	MEB392#1J-05***+++
0.0047	7.2	6.5	2.5	5	0.5	MEB472#1J-05***+++
0.0068	7.2	6.5	2.5	5	0.5	MEB682#1J-05***+++
0.0082	7.2	6.5	2.5	5	0.5	MEB822#1J-05***+++
0.01	7.2	6.5	2.5	5	0.5	MEB103#1J-05***+++
0.015	7.2	6.5	2.5	5	0.5	MEB153#1J-05***+++
0.022	7.2	6.5	2.5	5	0.5	MEB223#1J-05***+++
0.027	7.2	6.5	2.5	5	0.5	MEB273#1J-05***+++
0.033	7.2	6.5	2.5	5	0.5	MEB333#1J-05***+++
0.047	7.2	6.5	2.5	5	0.5	MEB473#1J-05***+++
0.056	7.2	6.5	2.5	5	0.5	MEB563#1J-05***+++
0.068	7.2	6.5	2.5	5	0.5	MEB683#1J-05***+++
0.082	7.2	6.5	2.5	5	0.5	MEB823#1J-05***+++
0.1	7.2	6.5	2.5	5	0.5	MEB104#1J-05***+++
0.12	7.2	6.5	2.5	5	0.5	MEB124#1J-05***+++
0.15	7.2	7.5	3.5	5	0.5	MEB154#1J-05***+++
0.18	7.2	7.5	3.5	5	0.5	MEB184#1J-05***+++
0.22	7.2	7.5	3.5	5	0.5	MEB224#1J-05***+++
0.27	7.2	7.5	3.5	5	0.5	MEB274#1J-05***+++
0.33	7.2	9.5	4.5	5	0.5	MEB334#1J-05***+++
0.39	7.2	9.5	4.5	5	0.5	MEB394#1J-05***+++
0.47	7.2	9.5	4.5	5	0.5	MEB474#1J-05***+++
0.56	7.2	11	6	5	0.5	MEB564#1J-05***+++
0.68	7.2	11	6	5	0.5	MEB684#1J-05***+++
0.82	7.2	11	6	5	0.5	MEB824#1J-05***+++
1	7.2	11	6	5	0.5	MEB105#1J-05***+++

100VDC (63VAC)

容量μF	W	H	T	P	d	產品代碼 Part No.
0.001	7.2	6.5	2.5	5	0.5	MEB102#2A-05***+++
0.0015	7.2	6.5	2.5	5	0.5	MEB152#2A-05***+++
0.0022	7.2	6.5	2.5	5	0.5	MEB222#2A-05***+++
0.0027	7.2	6.5	2.5	5	0.5	MEB272#2A-05***+++
0.0033	7.2	6.5	2.5	5	0.5	MEB332#2A-05***+++
0.0039	7.2	6.5	2.5	5	0.5	MEB392#2A-05***+++
0.0047	7.2	6.5	2.5	5	0.5	MEB472#2A-05***+++
0.0068	7.2	6.5	2.5	5	0.5	MEB682#2A-05***+++
0.0082	7.2	6.5	2.5	5	0.5	MEB822#2A-05***+++
0.01	7.2	6.5	2.5	5	0.5	MEB103#2A-05***+++
0.015	7.2	6.5	2.5	5	0.5	MEB153#2A-05***+++
0.022	7.2	6.5	2.5	5	0.5	MEB223#2A-05***+++
0.027	7.2	6.5	2.5	5	0.5	MEB273#2A-05***+++
0.033	7.2	6.5	2.5	5	0.5	MEB333#2A-05***+++
0.047	7.2	6.5	2.5	5	0.5	MEB473#2A-05***+++
0.056	7.2	6.5	2.5	5	0.5	MEB563#2A-05***+++
0.068	7.2	6.5	2.5	5	0.5	MEB683#2A-05***+++
0.082	7.2	7.5	3.5	5	0.5	MEB823#2A-05***+++
0.1	7.2	7.5	3.5	5	0.5	MEB104#2A-05***+++
0.12	7.2	7.5	3.5	5	0.5	MEB124#2A-05***+++
0.15	7.2	9.5	4.5	5	0.5	MEB154#2A-05***+++
0.18	7.2	9.5	4.5	5	0.5	MEB184#2A-05***+++
0.22	7.2	9.5	4.5	5	0.5	MEB224#2A-05***+++
0.27	7.2	9.5	4.5	5	0.5	MEB274#2A-05***+++
0.33	7.2	11	6	5	0.5	MEB334#2A-05***+++
0.39	7.2	11	6	5	0.5	MEB394#2A-05***+++
0.47	7.2	11	6	5	0.5	MEB474#2A-05***+++
0.56	7.2	11	6	5	0.5	MEB564#2A-05***+++
0.68	7.2	11	6	5	0.5	MEB684#2A-05***+++
0.82	7.2	11	6	5	0.5	MEB824#2A-05***+++
1	7.2	11	6	5	0.5	MEB105#2A-05***+++

注: # 表容量偏差 ; - 表引線型式 ; *** 表引線長度及包裝方式 ; +++ 表內部管理碼

Note: # Capacitance tolerance code ; - Forming lead shapes ; *** Lead length and packaging ; +++ Internal use

注: 本公司更改設計規格不予事先通知, 以上數據僅作選型參考, 以實際規格書為準

Note: Design, specifications are subject to change without notice, the above parameters for reference only, see the approval sheet for details.

注: 可依需求製作特殊規格

Note: Special size or items on request.

MEB (CL23B) series 小型化金屬化聚酯膜電容器

Miniaturized Metallized Polyester Film Capacitor



■外型尺寸 Dimensions (mm)

250VDC (160VAC)

容量μF	W	H	T	P	d	產品代碼 Part No.
0.001	7.2	6.5	2.5	5	0.5	MEB102#2E-05***+++
0.0015	7.2	6.5	2.5	5	0.5	MEB152#2E-05***+++
0.0022	7.2	6.5	2.5	5	0.5	MEB222#2E-05***+++
0.0027	7.2	6.5	2.5	5	0.5	MEB272#2E-05***+++
0.0033	7.2	6.5	2.5	5	0.5	MEB332#2E-05***+++
0.0039	7.2	6.5	2.5	5	0.5	MEB392#2E-05***+++
0.0047	7.2	6.5	2.5	5	0.5	MEB472#2E-05***+++
0.0068	7.2	6.5	2.5	5	0.5	MEB682#2E-05***+++
0.0082	7.2	6.5	2.5	5	0.5	MEB822#2E-05***+++
0.01	7.2	6.5	2.5	5	0.5	MEB103#2E-05***+++
0.015	7.2	6.5	2.5	5	0.5	MEB153#2E-05***+++
0.022	7.2	6.5	2.5	5	0.5	MEB223#2E-05***+++
0.027	7.2	7.5	3.5	5	0.5	MEB273#2E-05***+++
0.033	7.2	7.5	3.5	5	0.5	MEB333#2E-05***+++
0.047	7.2	7.5	3.5	5	0.5	MEB473#2E-05***+++
0.056	7.2	7.5	3.5	5	0.5	MEB563#2E-05***+++
0.068	7.2	9.5	4.5	5	0.5	MEB683#2E-05***+++
0.082	7.2	9.5	4.5	5	0.5	MEB823#2E-05***+++
0.1	7.2	9.5	4.5	5	0.5	MEB104#2E-05***+++
0.12	7.2	11	6	5	0.5	MEB124#2E-05***+++
0.15	7.2	11	6	5	0.5	MEB154#2E-05***+++
0.18	7.2	11	6	5	0.5	MEB184#2E-05***+++
0.22	7.2	11	6	5	0.5	MEB224#2E-05***+++

400VDC (200VAC)

容量μF	W	H	T	P	d	產品代碼 Part No.
0.001	7.2	6.5	2.5	5	0.5	MEB102#2G-05***+++
0.0015	7.2	6.5	2.5	5	0.5	MEB152#2G-05***+++
0.0022	7.2	6.5	2.5	5	0.5	MEB222#2G-05***+++
0.0027	7.2	6.5	2.5	5	0.5	MEB272#2G-05***+++
0.0033	7.2	6.5	2.5	5	0.5	MEB332#2G-05***+++
0.0039	7.2	6.5	2.5	5	0.5	MEB392#2G-05***+++
0.0047	7.2	6.5	2.5	5	0.5	MEB472#2G-05***+++
0.0068	7.2	7.5	3.5	5	0.5	MEB682#2G-05***+++
0.0082	7.2	7.5	3.5	5	0.5	MEB822#2G-05***+++
0.01	7.2	9.5	4.5	5	0.5	MEB103#2G-05***+++
0.015	7.2	9.5	4.5	5	0.5	MEB153#2G-05***+++
0.022	7.2	9.5	4.5	5	0.5	MEB223#2G-05***+++
0.027	7.2	11	6	5	0.5	MEB273#2G-05***+++
0.033	7.2	11	6	5	0.5	MEB333#2G-05***+++
0.047	7.2	11	6	5	0.5	MEB473#2G-05***+++

注:# 表容量偏差 ; - 表引線型式 ; *** 表引線長度及包裝方式 ; +++表內部管理碼

Note: # Capacitance tolerance code ; - Forming lead shapes ; *** Lead length and packaging ; +++ Internal use

注:本公司更改設計規格不予事先通知,以上數據僅作選型參考,以實際規格書為準

Note: Design, specifications are subject to change without notice, the above parameters for reference only, see the approval sheet for details.

注:可依需求製作特殊規格

Note: Special size or items on request.